

DEGACOTE C4

SECTION 2

CONCRETE SEALER



PRODUCT INFORMATION BULLETIN

September 2011

DESCRIPTION

Degacote C4 is a U.V. stable, solvent based Acrylic Polymer specially formulated for the sealing of concrete surfaces.

USE

As a clear or coloured coat on concrete floors, driveways, paths and other masonry products. It seals the porous surface, enhances the appearance, eliminates dusting and ensures easy cleaning.

APPLICATION

By brush, roller, soft hair broom or airless spray.

CLEAN UP

Degacote Solvent 100.

APPLICATION RATE

0.15 - 0.2 Litres/sq metre depending on absorbency of concrete surface.

CURING TIME

30 minutes at 20°C.

RECOAT TIME

60 minutes.

For any further details contact us on 03 9725 9590.

TERMS AND CONDITIONS OF SALE

All statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy of completeness thereof is not guaranteed, and the following is made in lieu of all warranties, express or implied.

Sellers and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for injury, loss or damage, direct or indirect or consequential, arising out of the use of or the inability to use the product. Before using, user shall determine the suitability of the product for his intended use, and user assumes all risk and liability whatsoever in connection therewith.

Statements or recommendations not contained herein shall have no force or effect unless in an agreement signed by officers of seller and manufacturer.