

DESCRIPTION

Sprayable Degadur SP3 is a two component cold applied plastic coating suitable for application to a wide range of surfaces.

USE

As a clear or pigmented coating in most bitumen, primed concrete, timber and metal surfaces. It provides a tough, waterproof, flexible hard wearing coating suitable for use in:

- Roadmarking application
- The chemical industry
- General industry
- Civil engineering
- The transport industry

(Refer application instructions for more detail.)

APPLICATION

Applied by specialised, 1:1 ratio, two component airless spraying equipment either hand held or machine mounted for use in roadmarking applications.

CLEAN UP

Degacote Cleaning Solvent or general purpose thinners.

APPLICATION RATE

Depends on the application.

Generally sprayed, 1 litre per square metre as a base or aggregate holding coat, and 0.5 litre per square metre as a top coat.

CURING TIME

Can be varied to suit application.

At 20°C: 10 minutes for roadmarking.
30 minutes as a general coating.

COLOUR RANGE

Clear, white, black, traffic yellow, other colours by request.

Ref:TCP Product Sheets\Sprayable Degadur SP3.doc(hg)

MELBOURNE

1 Shelley Court
Kilsyth Vic 3137
Ph (03) 9725 9590

BRISBANE

1/18 Boron Street
Sumner Park Qld 4074
Ph (07) 3376 6700

SYDNEY

P.O. BOX 499
Swansea NSW 2281
Ph 0403 266 780